NULLCORR

SOLUTIONS FOR A STRONGER TOMORROW

TECHNICAL DATA SHEET

STRIPPRO

Gel paint remover | Vertical and horizontal surfaces

GEL	2–15 min	3–5 m²/kg	READY
PHYSICAL STATE	TYPICAL SOFTENING TIME	COVERAGE	TO USE

01 PRODUCT OVERVIEW

NullCorr StripPro is a paint remover used to soften and remove existing paint films from surfaces.

02 FEATURES AND BENEFITS

Its gel-like consistency allows use on both vertical and horizontal surfaces. It penetrates deeply into thick paint layers, softening and removing the paint without damaging the underlying surface.

03 TECHNICAL SPECIFICATIONS

PROPERTY	VALUE / DESCRIPTION
Physical state	Gel
Density at 20 °C	1.14 ± 0.01 g/ml
Typical softening time	2–15 minutes
Thinning	Ready to use
Coverage	3–5 m²/kg, depending on paint film thickness
Packaging	1 L / 12 L
Storage temperature	5–25 °C
Shelf life	1 year in original packaging

04 APPLICATION SURFACES

Suitable for softening and removing all types of paint from surfaces such as metal, plaster, stone, wood and concrete.

Industrial Coatings Africa
Block KS33 Klan Street, off Dadeban Road, Adjacent
Promasidor Gh. Ltd. (Cowbell), North Industrial Area, Accra, Ghana
+233 50 765 6464 | +233 25 602 5000 | +233 25 602 5001 | +233 243 12 5882
www.industrialcoatingsafrica.com

STRIPPRO

Application | Storage | Safety | Document information

05 APPLICATION METHOD

STEP	METHOD
1. Apply	Apply NullCorr StripPro to the paint film using a brush. Apply thicker coats to old and thick paint layers.
2. Allow to soften	Effectiveness depends on the thickness, flexibility and age of the paint film. Generally, the paint softens within 2–15 minutes.
3. Remove paint	Scrape off the softened coating with suitable tools, such as a spatula, or remove it using pressurized water.
4. Clean and dry	Clean the surface with water and detergent. Before repainting, thoroughly clean the surface and allow it to dry completely.

06 STORAGE AND SHELF LIFE

Store in original packaging for up to **1 year** at **5–25 °C**, away from direct sunlight. Protect from excessive heat, moisture and freezing.

07 IMPORTANT WARNINGS

- Keep away from sources of ignition. Smoking is prohibited near the product.
- Do not leave containers open for extended periods.
- Use only in well-ventilated areas.
- Wear appropriate protective equipment, including gloves, a mask and safety goggles during application.

08 MANUFACTURER AND DOCUMENT INFORMATION

Manufacturer: Yalaz Boya, Turkey
Product: NullCorr StripPro - Paint Remover
Distributor: Industrial Coatings Africa
Source TDS date: 10 March 2026 | **Revision:** 00

Industrial Coatings Africa
Block KS33 Klan Street, off Dadeban Road, Adjacent
Promasidor Gh. Ltd. (Cowbell), North Industrial Area, Accra, Ghana
+233 50 765 6464 | +233 25 602 5000 | +233 25 602 5001 | +233 243 12 5882
www.industrialcoatingsafrica.com